



# Replacement Instructions

## CBTM1

**Please ensure you have read the instructions and that no parts are missing prior to installation.**

### **Please note**

The approximate life of your filter is two years and will vary depending on several factors, i.e. manufacturers recommendation, amount of water being used through the filter, turbid water supply, amount of sediment in the water etc. If the flow through the filter decreases or water taste deteriorates it may be time to replace the filter.

How do you know when it's time to replace your cartridge? We place your name in our records; this allows us to remember when you received your new cartridge. We will then remind you when it is time to replace it.

**To change the AFRL to the DVLPL; pull on the white tubing to remove it from the AFRL fitting, if it is too tight you can loosen it in hot water**

**For support please phone our technical support team on 0800 787 342**

### **Step one**

Keep kitchen tap turned off.

### **Step two**

Hold base of benchtop unit firmly and unscrew base off old filter.

### **Step three**

Unscrew the spout off old filter.

### **Step four**

Re-screw the new filter onto the base with flow direction arrow pointing upwards.

### **Step five**

Then screw the spout on to the new filter.

### **Step six**

Make sure everything is sealed correctly.

### **Step seven**

Turn water supply on and run filter for approximately 5 minutes to activate the filter. **Note:** the water may flow black for the first few seconds. This is only carbon dust and will clear quickly. The water may have a milky look for the first few hours; this is due to millions of air bubbles being forced from the carbon.

### **Universal Rubber (AFRL)**

To use your purifier, push the universal rubber connection onto your tap. Aim faucet spout of purifier into sink.

Turn tap on slowly (too much pressure will blow the rubber off the tap) the purifier housing will fill with water, then start to flow from the spout. Continue to flush water through the filter for 3 to 5 minutes; which will activate the filter.

### **Diverter valve (DVLPL)**

To install the diverter valve onto your tap, remove aerator from tap, screw diverter valve onto faucet. If the diverter does not fit, try the enclosed adaptor, between the faucet and diverter.

To use your water filter, turn your tap on, switch diverter on and follow instructions 2 to 5 above.

